


Fairland Group Limited

Room 2315-2317, No.69, Xianlie Road Central Guangzhou,
P.R.China 510095







ORIGINAL FULL-INVERTER TECH

Brings Long Endurance

Precise coordination of 3 motors



The core control system well coordinates the running power of 3 DC motors between 20%~100% (averagely 50%), making them perfectly match each other to realize longer endurance.

Adjustable suction & running power



In different pool environments of debris & friction increased, wall climbing, etc, the advanced control system will intelligently adjust the most suitable motor running speed to bring the best flow and cleaning effect with the lowest energy consumption.





PATENTED "3D S" PATH

Brings Double Coverage Efficiency



EYES: 1 Precise Gyro + 6 Sensors Spatial Detecting & Data Collecting


Outputting real-time location and direction of X20 Robot




BRAIN: Self-developed algorithm
Continuous Analyzing & Commanding

Automation of location adjustments, anti-bump and 90° turning

The intelligent program makes sure X20 Robot drive in the most efficient "3D S" cleaning path, which brings double coverage efficiency.



3



X20 Robot

Others

AI TIMER

1 Charge for 2 Weeks Cleaning

Enjoy a totally free vacation

Automatically restart as the customized setting, X20 Robot will guard your pool with 2 weeks' continual cleaning!







Full-covered Cleaning Active wall climbing and waterline scrubbing

- Magnetic Filter Basket
 Top access for easy extraction
- Smart App Control

 Multi-function setting

MORE FEATURES



Specifications of X20 Robot

Model	R100	R80	R60	R45	R30
Picture	Car	TOR	CON	CAN P	CON
Performance codition reference:Floo	or mode in Liner pool				
Endurance time	10h	8h	6h	4.5h	3h
Performance codition reference: Floo	or/wall/waterline mode in Liner pool				
Endurance time	6h	4.5h	3.5h	2.5h	2h
Charging time	10h	8h	6h	4.5h	3h
Pool size	12×10m	12×10m	12×10m	12×10m	12×10m
Optimum pool temperature	4~35°C	4~35°C	4~35°C	4~35°C	4~35°C
Cleaning mode	Floor only;Floor/wall/waterline				
Cleaning cycle	0.5h/1h/2h/Max	0.5h/1h/2h/Max	0.5/1h/2h/Max	0.5/1h/2h/Max	0.5/1h/2h/Max
Al Timer	YES	YES	YES	YES	YES
App connection	YES	YES	YES	YES	YES
Filter capacity	3.2L	3.2L	3.2L	3.2L	3.2L
Filteration accuracy	180µm	180μm	180μm	180μm	180μm
Pump flow rate	22~15m³/h	22~15m³/h	20~15m ³ /h	20~15m³/h	20~15m³/h
Running power	30~110W	30~110W	30~110W	30~110W	30~110W
Moving speed	12m/min	12m/min	12m/min	12m/min	12m/min
Motor number	3	3	3	3	3
Charger Input	100-240VAC~50/60Hz				
Running voltage/current	25.2V/1.2A	25.2V/1.2A	25.2V/1.2A	25.2V/1.2A	25.2V/1.2A
Robot dimension	495*395*265mm	495*395*265mm	495*395*265mm	495*395*265mm	495*395*265mm
Robot N.W/G.W	12kg/17kg	12kg/17kg	12kg/17kg	11.5kg/16.5kg	11.5kg/16.5kg
Warranty	2 years	2 years	2 years	2 years	2 years

^{*}Reference: Above endurance time is based on 2 hours' cleaning each time in liner pool

Cleaning Time Reference (Take a 4*8m liner pool for example):

^{1.} Clean the floor once: 20 minutes

^{2.} Clean the whole pool (floor/wall/waterline) once: 40 minutes